

## DOOR HARDWARE

- JUNCTION BOX BY OTHERS
- NOT USED
- VON DUPRIN QEL / FALCON FIRE RATED MEL EXIT DEVICE (24 VDC)
- LCN 8310-804 DOOR SAFETY SENSOR
- NOT USED
- LCN SENIOR SWING AUTO DOOR OPERATOR
- LCN SINGLE GANG BOX TOUCHLESS ACTUATORS
- VON DUPRIN PS902 X 900-2RS X 900-BBK
- (9) VON DUPRIN ELECTRIC POWER TRANSFER

## WIRE REQUIREMENTS

2/18 AWG STRANDED FOR EXIT DEVICE FROM POWER SUPPLY 4/18 AWG STRANDED FROM INTERIOR ACTUATOR DIRECT TO P6
4/18 AWG STRANDED FROM EXTERIOR ACTUATOR DIRECT TO P7 2/20 AWG STRANDED FROM P10 CABLE TO POWER SUPPLY RELAY 4/18 AWG STRANDED FROM SAFETY SENSOR (PUSH SIDE) TO P3 4/18 AWG STRANDED FROM SAFETY SENSOR (PULL SIDE) TO P2

\*\*ANY WIRE RUNS GREATER THAN 200 FEET VERIFY GAUGE WITH MANUFACTURER.\*\*

## GENERAL NOTES:

ALL LOW VOLTAGE WIRE TO RUN IN MINIMUM 3/4" CONDUIT OR INSIDE DRYWALL UNLESS NOTED OTHERWISE

ALL LOW VOLTAGE WIRE TO BE STRANDED WIRE

ALL GANG BOXES BY ELECTRICAL CONTRACTOR AS REQUIRED ALL LOW VOLTAGE WIRING TO BE LABELED CLEARLY AT BOTH END ALL MOUNTING HEIGHTS AS SHOWN

COORDINATE MOUNTING LOCATIONS WITH ELECTRICAL/ARCHITECTURAL PLANS
ANY DEVIATION FROM HARDWARE SPECIFIED IN SECTION 08710 WILL NEGATE ALL REQUIREMENTS SHOWN
HEREIN AND REQUIRE NEW DRAWINGS BY OTHERS TO MATCH SUBSTITUTED HARDWARE

## OPERATIONAL DESCRIPTION:

DOOR NORMALLY CLOSED AND LOCKED.
TOUCHLESS ACTUATORS ON EITHER SIDE OF DOOR WILL CAUSE QEL EXIT DEVICE TO
RETRACT LATCH AND DOOR OPEN FOR PREDETERMINED AMOUNT OF TIME.
SAFETY SENSOR ON "SAFETY SIDE – PULL SIDE" OF DOOR TO PREVENT PERSON OR OBJECT FROM BEING STRUCK BY DOOR
SAFETY SENSOR ON "APPROACH SIDE – PUSH SIDE" OF DOOR TO PREVENT PERSON OR OBJECT FROM STRUCK BY DOOR WHILE IN THE OPENING. FREE EGRESS AT ALL TIMES.

	ELEVATION DRAWING		
ALLEGION	Drawn By: Jason Relyea DHT, DHC		Checked by:
ELECTRIFIED ELEVATION	DATE: 03-15-2021	VERSION:	DRAWING NO: 100/17
DRAWINGS	SCALE: N.T.S.	REVISION:	1004/

Wiring Diagram Terms of Use: This information is for professional use only and is intended to be a guide for proper product application and specification. See specific product manuals for proper installation. Any installation should be performed by persons qualified to perform electrical work and in compliance with applicable codes, rules, regulations and orders. Allegion reserves the right to change or modify the information herein without notice. No warranties, express or implied, are provided by Allegion as a result of this information. Any and all use and reproduction of the information herein except for product application and specification is expressly forbidden.

Copyright 2021 Schlage Lock Company LLC.