

N.T.S.

#### DOOR HARDWARE

- JUNCTION BOX BY OTHERS
- SCHLAGE 679-05 DOOR POSITION SWITCH
- SCHALGE M400 SERIES MAGLOCK
- SCHLAGE MT11 OR MT15
- SCHLAGE 620 SERIES DELAYED ACTION PUSHBUTTON OVER-RIDE
- PIR RX MOTION SENSOR
- VON DUPRIN PS902 X 900-2RS X 900-FA

#### WIRE REQUIREMENTS

2/20 AWG STRANDED FOR DPS

2/18 AWG STRANDED FOR MAGNETIC LOCK POWER 2/18 AWG STRANDED FOR PUSHBUTTON OVER-RIDE

MAGLOCK POWER TO INTERRUPTED THROUGH DELAYED ACTION PUSHBUTTON OVER-RIDE

4/18 AWG STRANDED FOR RX MOTION SENSOR 2/18 FOR POWER

2/18 FOR SIGNAL / DE-ENERGIZE MAGLOCK
6/22 AWG SHIELDED TO CARD READER. VERIFY
REQUIREMENTS W/ CARD READER MANUFACTURER.

REQUIREMENTS W/ CARD READER MANUFACTURER.

2/18 AWG STRANDED FOR NORMAL CLOSED FIRE ALARM CONTACT
DIRECT INTERRUPT OF POWER TO MAGLOCK

PLENUM RATED CABLE FROM ACCESS PANEL TO J-BOX
INTEGRATOR TO VERIFY REQUIREMENTS AND PROVIDE
AS REQUIRED FOR SYSTEM DESIGN.

\*\*RX SWITCH, FIRE ALARM CONTACTS, ACCESS CONTROL RELAY AND
PUSHBUTTON TO ALL BE WIRED IN SERIES OF THE POWER PROVIDED
TO MAGLOCY. TO MAGLOCK

\*\*ANY WIRE RUNS GREATER THAN 200 FEET VERIFY GAUGE WITH MANUFACTURER.\*\*

### GENERAL NOTES:

ALL LOW VOLTAGE WIRE TO RUN IN MINIMUM 3/4" CONDUIT OR INSIDE DRYWALL UNLESS NOTED OTHERWISE

ALL LOW VOLTAGE WIRE TO BE STRANDED WIRE
ALL GANG BOXES BY ELECTRICAL CONTRACTOR AS REQUIRED
ALL LOW VOLTAGE WIRING TO BE LABELED CLEARLY AT BOTH END
ALL MOUNTING HEIGHTS AS SHOWN

ACC MODITION THEORITIS AS SHOWN
COORDINATE MOUNTING LOCATIONS WITH ELECTRICAL/ARCHITECTURAL PLANS
ANY DEVIATION FROM HARDWARE SPECIFIED IN SECTION 08710 WILL NEGATE ALL REQUIREMENTS SHOWN HEREIN AND REQUIRE NEW DRAWINGS BY OTHERS TO MATCH SUBSTITUTED HARDWARE

## OPERATIONAL DESCRIPTION:

DOORS NORMALLY CLOSED AND LOCKED.

PRESENT VALID CREDENTIAL TO CARD READER TO RELEASE MAGLOCK. TIME DETERMINE BY ACCESS CONTROL SYSTEM.

CONTROL STSIEM.

RX MOTION SENSOR TO SHUNT DOOR FORCED ALARM, DE-ENERGIZE MAGLOCK FOR FREE EGRESS.

EMERGENCY OVER-RIDE PUSHBUTTON TO BE LOCATED WITHIN 5 FEET OF OPENING

ON FIRE ALARM, MAGNETIC LOCK TO DE-ENERGIZE ALLOWING FREE EGRESS.

intended to be a guide for proper product application and specification. See specific product manuals for proper installation. Any installation should be performed by persons qualified to perform electrical work and in compliance with applicable codes, rules, regulations and orders. Allegion reserves the right to change or modify the information herein without notice. No warranties, express or implied, are provided by Allegion as a result of this information. Any and all use and reproduction of the information herein except for product application and specification is expressly forbidden.

Wiring Diagram Terms of Use: This information is for professional use only and is

Copyright 2021 Schlage Lock Company LLC.

# ALLEGION **ELECTRIFIED ELEVATION**

**DRAWINGS** 

**ELEVATION DRAWING** 

By: Jason Relyea DHT, DHC 03-15-2021 N.T.S