



LENGTH	DIM. "A"	DIM. "B"
20 1/2" (520)	10" (254)	13" (330)
25 1/2" (648)	14 1/4" (362)	17 1/4" (438)
30 1/2" (775)	18 1/2" (470)	21 1/2" (546)

	QTY	SCREW DETAILS
FRAME	4	#10 X 1 1/4" FPHSMS
DOOR - STANDARD	4	#10 X 1 1/4" FPHSMS
DOOR - SEX BOLT	4	SEX BOLTS
	4	10-24 X 5/8" FPHMS
DOOR - THRU BOLT	4	10-24 X 2 1/4" FPHMS
	4	10-24 CAP NUTS
	4	#10 WASHERS

NOTE:

1. DIMENSIONS A AND B ARE FOR INSTALLATIONS TO STEEL DOOR FRAMES WITH DIMENSIONS AS SHOWN.
2. HOLLOW METAL DOORS AND FRAMES SHOULD BE REINFORCED WITH A MINIMUM OF 14 GAUGE.

IVES

CS115 CRASH STOP
INSTALLATION TEMPLATE

ALLEGION

NOTE: DIMENSIONS IN () ARE IN MILLIMETERS

TEMPLATE
NUMBER: INST.CS115(B)

Date:
7-11-22