

## **VON DUPRIN**.

# AX exit devices

Featuring the 98/99, 94/95, 33/35A and 22 Series devices

# The exit device that requires only 5 pounds of force to operate

The AX was born out of a need to provide the market with a solution that meets the 2010 ADA Standards for Accessible Design (Chapters 404.2.7 and 309.4) that state the force reqiured to activate operable parts shall be 5 pounds maximum. The 2013 California Building Code (Chapter 11B-309.4) adopted virtually identical requirements that went into effect January 1st, 2014, and has been carried forward into subsequent editions of the CBC.


Since pioneering the first exit device in 1908, Von Duprin life safety products have provided unparalleled quality, performance and flexibility for schools, hospitals, stadiums and public buildings. These products come with the support and customer care only offered by Von Duprin, providing the confidence and peace of mind at critical moments of life safety.

#### AX device code compliance

- ANSI/BHMA A156.3
- 2010 ADA Standards for Accessible Design (Chapters 404.2.7 and 309.4)
- California Building Code (Chapter 11B-309.4)]
- UL305 Panic Exit
- UL305, UL10C Fire Exit Hardware



## How to identify the Von Duprin AX device



In the field, look for the compliance note on the UL label and the AX device label. Both labels can be found on the center case cover of the exit device as shown below.



PH1295-00 VON DUPRIN 33A SERTIES ISSUE NO 0083314 Building Code (2013) Sec. 118-309.4

UL label

Contact Allegion today at 877-671-7011 or us.allegion.com to learn how the AX device can help you provide accessibility without compromise.

AX98/99 Series	specifications			
Device types	AX98/99 - Rim AXXP98/99 - Rim AX98/9927 - LBR AX98/9950 WDC - LBL AX98/9950 WDC - LBL AX98/9949 - LBL and LBL-AFL - Concealed Vertical Cable Less Bottom Latch			
Device functions	EO, DT, NL, NLOP, L, LBE, LDT, LNL			
Device lengths	3'/4'			
Rating	Panic and Fire			
Electric options	QELX - Quiet Electric Latch Retraction for AX LX - Latchbolt monitor switch LXLC - Latchbolt monitor switch low current LXRX - Latchbolt pushpad monitor LXRXLC - Latchbolt pushpad monitor low current RX - Pushpad monitor switch RXLC - Pushpad monitor switch low current RX2 - Double pushpad monitor switch ALK - Alarm kit SS - Signal switch			
Mechanical options	GBK - Glass bead kit -2 - Double cylinder -2SI - Double cylinder with Security Indicator QM - Quiet Mechanical SNB - Sex bolts SEC - Security screws WP - Weep holes			
Dogging options*	Hex key dogging = Standard CD - Cylinder dogging CDSI - Cylinder dogging with Security Indicator DI - Dogging indicator HDSI - Hex dogging with security indicator LD - Less dogging SD - Special dogging			
AX94/95 Series	specifications			
Device types	AX94/9547			
Device functions	EO, DT, L, LDT, LBE, LNL			
Device lengths	3'/4'			
Rating	Panic and Fire			
Electric options	LX - Latchbolt monitor switch			

AX33/35A Serie	s specifications
Device types	AX33/35A - Rim AX33/3549 - LBL & LBL-AFL - Concealed Vertical Cable Less Bottom Latch
Device functions	EO, DT, NL, NLOP, L, LBE, LDT
Device lengths	3'/4'
Rating	Panic and Fire
Electric options	QELX - Quiet Electric Latch Retraction for AX LX - Latchbolt monitor switch LXLC - Latchbolt monitor switch low current LXRX - Latchbolt pushpad monitor LXRXLC - Latchbolt pushpad monitor low current RX - Pushpad monitor switch RXLC - Pushpad monitor switch low current RX2 - Double pushpad monitor switch ALK - Alarm kit SS - Signal switch
Mechanical options	GBK - Glass bead kit QM - Quiet Mechanical SEC - Security screws WP - Weep holes
Dogging options*	Hex key dogging = Standard CD - Cylinder dogging CDSI - Cylinder dogging with Security Indicator HDSI - Hex dogging with security indicator LD - Less dogging
AX22 Series spe	cifications
Device types	AX22 - Rim AX2227 - LBR
Device functions	EO, DT, NL, NLOP, L, LBE
Device lengths	3'/4'
Rating	Panic and Fire
Electric options	LX - Latchbolt monitor switch RX - Pushpad monitor switch RX2 - Double pushpad monitor switch ALK - Alarm kit
Mechanical options	GBK - Glass bead kit
Dogging options*	Hex key dogging = Standard LD - Less dogging

\*For panic devices only

## Ordering information

AX	- 98		- L -	F	2	-US26D	) - 3'	-RHR -	996L	-06-	SNB
Prefix	Series	Device type	Function	Rating	Sufflix	Finish	Door Width	Handing	Trim	Lever Style	Accessories
1	2	3	4	5	6	7	8	9	10	11	12

#### Selections correspond with the numbers above. See price book for specific configuration options.

	Prefix	3	Device type	7	Finish	
X*	Accessible Device	N/A	Rim		See pricebook for finish offering	
<b>ZELX</b>	Quiet Electric Latch Retraction for AX	27	Surface Vertical Rod	8	Door Width	
)M DSI	Quiet Mechanical Cylinder dogging with Security Indicator	47 49	Concealed Vertical Rod Concealed Vertical Cable	3'	Standard Default	
IDSI	Hex dogging with Security Indicator	4 Function		4'		
Х	Latchbolt Monitor Switch Latchbolt Monitor Switch Low Current Latchbolt Pushpad Monitor			9	Handing	
XLC		EO DT	Exit Only Dummy Trim	RHR	Right Hand Reverse	
KRX		NL	Night Latch	LHR	Left Hand Reverse	
XRXLC	Latchbolt Pushpad Monitor	NLOP	Night Latch - Optional Pull Lever Lever - Blank Escutcheon	10	Trim	
	Low Current Pushpad Monitor Switch C Pushpad Monitor Switch Low Current	L LBE		See pricebook for trim/control offering		
X		LDE	Lever, Rigid - Dummy Trim	11	Lever style	
ALC		LNL	Lever, Rigid - Night Latch	See pricebook for lever style offering		
X2	Double Pushpad Monitor Switch	5	Rating	12	Accessories	
S	Signal Switch	N/A Panic		ALK	Alarm Kit	
Must be specified; may select more than one prefix.		F	Fire-rated	GBK	Glass Bead Kit	
	Series	6	Suffix	SNB	Sex Bolts	
(P98 98	Series 98 - smooth		Double Cylinder	Contact Allegion today at 877-671-7011 or us.allegion.com to learn how the		
8 P99			Double Cylinder with Security Indicator			
9	Series 99 - grooved	LBL	Less Bottom Latch	AX device can help you provide		
	Series 94 - smooth	LBR	Less Bottom Rod	accessibility without compromise.		
	Series 95 - grooved	LBL-AFL				
3A	Series 33A - grooved	WH	Weep Holes			
5A	Series 35A - smooth					
2	Series 22					

Allegion, the Allegion logo, ENGAGE technology, the ENGAGE technology logo, Schlage and the Schlage logo are trademarks of Allegion plc, its subsidiaries and/or affiliates in the United States and other countries. All other trademarks are the property of their respective owners.

### **About Allegion**

Allegion (NYSE: ALLE) is a global pioneer in safety and security, with leading brands like CISA®, Interflex®, LCN®, Schlage®, SimonsVoss® and Von Duprin®. Focusing on security around the door and adjacent areas, Allegion produces a range of solutions for homes, businesses, schools and other institutions. Allegion is a \$2 billion company, with products sold in almost 130 countries. For more, visit **www.allegion.com.** 



© 2020 Allegion 010333 Rev. 9/20 www.allegion.com/us