

**LOCKNETICS™**

## WMG Series

Weather-resistant  
electromagnetic locks



### Overview


The WMG Series of weather-resistant, surface mounted electromagnetic locks are designed for high profile openings that require a tamper-resistant lock with an aesthetically pleasing appearance. A stainless steel housing, fire-rated epoxy seal, optional mounting bracket and an assortment of brackets enable the WMG Series to be used in a variety of applications. Model options give you up to 600 lb. or 1200 lb. holding strength.

### Features and benefits


- 600 lb. hold force model for traffic control applications
- 1200 lb. hold force model for high security applications
- Sealed with fire-rated epoxy for weather- and tamper-resistant applications
- Mounting plate for safe, simple installation
- Magnetic bond sensor included
- Built-in voltage spike suppressor
- Field selectable 12/24 VDC
- Stainless steel housing in 630/US32D satin finish
- Suitable for outdoor use
- 5-year limited warranty

# WMG Series

## WMG600 dimensions



## WMG1200 dimensions



## Electromagnetic lock specifications

Specification	WMG600	WMG1200
Holding force	600 lb.	1200 lb.
Input voltage (field selected)	12/24 VDC	12/24 VDC
Current draw (amps standard unit)	12 VDC @ 0.5A 24 VDC @ 0.25A	12 VDC @ 0.5A 24 VDC @ 0.25A
BHMA finish	630 Satin Stainless Steel	630 Satin Stainless Steel
Height	1 <sup>23</sup> / <sub>32</sub> " (43.5mm)	2 <sup>11</sup> / <sub>16</sub> " (68mm)
Length	8" (203mm)	8 <sup>11</sup> / <sub>16</sub> " (220mm)
Depth	1 <sup>9</sup> / <sub>16</sub> " (40mm)	1 <sup>5</sup> / <sub>8</sub> " (42mm)
Armature dimensions (each)	7 <sup>5</sup> / <sub>16</sub> " x 1 <sup>3</sup> / <sub>4</sub> " x 9/ <sub>16</sub> " (185mm x 45mm x 14mm)	7 <sup>1</sup> / <sub>4</sub> " x 1 <sup>3</sup> / <sub>8</sub> " x 5/ <sub>8</sub> " (185mm x 61mm x 16mm)
Weight	3.24 lbs.	5.43 lbs.
Certifications	UL1034, UL10C (single door), UL294	UL1034, UL10C (single door), UL294
Temperature	-31° to +150.8°F (-35° to +66°C)	-31° to +150.8°F (-35° to +66°C)

## Optional accessories

- Z bracket for inswinging doors
- L bracket for narrow frame and outswinging doors
- 1/2" and 5/8" filler plates

### WLBK600 - L bracket



### WLBK1200 - L bracket



## WMG Series ordering and accessories

Product name	Product description	Finish	Ordering UPC
WMG600	Weatherproof mag lock - 600lb	630/US32D	043156646098
WMG1200	Weatherproof mag lock - 1200lb	630/US32D	043156646142
<b>Z-brackets</b>			
WZBK600	Z-bracket sets - 600lb	628/US28	043156646104
WZBK1200	Z-bracket sets - 1200lb	628/US28	043156646159
<b>L-brackets</b>			
WLBK600	L-bracket - 600lb	628/US28	043156646111
WLBK1200	L-bracket - 1200lb	628/US28	043156646166
<b>Filler plates</b>			
WFP50	1/2" Filler plate	628/US28	043156646128
WFP63	5/8" Filler plate	628/US28	043156646135

### WZBK600 - Z bracket set



### WZBK1200 - Z bracket set



Allegion, the Allegion logo, Locknetics and the Locknetics logo are trademarks of Allegion plc, its subsidiaries and/or affiliates in the United States and other countries. All other trademarks are the property of their respective owners.

## About Allegion

Allegion (NYSE: ALLE) is a global pioneer in seamless access, with leading brands like CISA®, Interflex®, LCN®, Schlage®, SimonsVoss® and Von Duprin®. Focusing on security around the door and adjacent areas, Allegion secures people and assets with a range of solutions for homes, businesses, schools and institutions. Allegion had \$2.9 billion in revenue in 2019 and sells products in almost 130 countries. For more, visit [www.allegion.com](http://www.allegion.com)

KRYPTONITE ■ LCN ■  ■ STEELCRAFT ■ VON DUPRIN



© 2021 Allegion  
013790, Rev. 04/21  
[www.allegion.com/us](http://www.allegion.com/us)