

700 Series

Pushbuttons



Overview

Schlage pushbuttons are used to control the egress of a door. The 700 Series pushbuttons are easy to install, entry level pushbuttons that are designed to meet commercial applications. Use with indoor swinging or sliding doors that are electrically or electronically locked. 700 Series entry level pushbuttons are available for single gang and narrow stile applications. The 709 model includes backlit buttons with "PUSH TO EXIT" or handicap symbol to meet ADA requirements for the ingress or egress of a door.

Features & Benefits

- Illuminated 2" square large button options or 5/8" and 7/8" round button options
- Optional dual LED status indicators in green and red
- For indoor use
- Momentary switch standard or factory orderable with maintained (alternate action) switch
- Handicapped symbol option
- Single gang or narrow style faceplate cover options
- Satin stainless steel finish
- UL 294 Listed

700 Series Pushbutton Specifications

Specification	701	709
Contact ratings	3A @ 30VAC/VDC, momentary SPDT contacts	5A @ 30VAC/VDC, momentary SPDT contacts
Wire leads	20 awg – 6" long	20 awg – 8" long
Input requirements with LED option		
Voltage	12/24 VDC	12/24 VDC
Current draw	30 mA	30 mA
Wire leads	24 awg – 6" long	24 awg – 6" long
Input requirements with ILL option		
Voltage	24 VDC	12/24 VDC

Ordering Information

- **701RD** - 7/8" Red mushroom button
- **701BK** - 7/8" Black mushroom button
- **701RD EX** - 5/8" Red button - engraved "PUSH TO EXIT"
- **701RD EX ILL** - 5/8" Red button - illuminated "PUSH TO EXIT"
- **709RD EX ILL** - 2" Red square - illuminated "PUSH TO EXIT"
- **709GR EX ILL** - 2" Green square - illuminated "PUSH TO EXIT"
- **709BLH ILL** - 2" Blue square - illuminated handicapped symbol

Options

- **L2** - Two LEDs, red and green, dual voltage for status indication
- **AA** - Alternate action - maintained (701 Series only)
- **NS** - Narrow stile plate (701 Series only)