



Credentials

compatible with Schlage
Control™ Smart Locks



Overview

Schlage Control™ Smart Locks mark a new era of electronic access control in the multi-family world. Without traditional keys to deal with, properties will save time and money in managing resident doors. Compatible with Schlage™ smart and multi-technology credentials (MIFARE Classic®, MIFARE Plus®, and MIFARE® DESFire® EV1), Schlage Control Smart Locks require 1K byte of available smart credential memory capacity.

Smart credentials

Schlage contactless smart credentials put you in control by delivering smarter solutions. These credentials protect your most sensitive data by utilizing extra layers of security protection, and can be used for many other applications including transit, cashless vending, and cafeteria point of sale. Schlage contactless smart credentials operate on a 13.56 MHz frequency, and utilize high security encrypted data, which is mutually authenticated in communication between the card and reader, providing optimum security.

Multi-technology credentials

Schlage multi-technology credentials are extremely flexible. Particularly useful during a transition from proximity technology to smart technology, this card can be read by both proximity readers and smart readers. This allows customers to economically migrate to the latest smart technology utilized by Schlage Control Smart Locks at their own pace. Schlage multi-technology credentials contain both 125 kHz proximity and 13.56 MHz contactless smart card capability in one unit.



13.56 MHz

Smart credentials¹

Model number	9451	8420	9551	5551	8520	9651	8620	9651T	5651T
Credential type	Clamshell	Clamshell	ISO glossy white ²	ISO glossy white ²	ISO glossy white ²	Keyfob	Keyfob	Thin keyfob	Thin keyfob
Credential technology; ISO standard	MIFARE Classic; ISO 14443	MIFARE DESFire EV1; ISO 14443	MIFARE Classic; ISO 14444	MIFARE Plus SE; ISO 14443	MIFARE DESFire EV1; ISO 14443	MIFARE Classic; ISO 14443	MIFARE DESFire EV1; ISO 14443	MIFARE Classic; ISO 14443	MIFARE Plus SE; ISO 14443
Dimensions (H x W x T in inches)	3.37" x 2.125" x 0.075"	3.37" x 2.125" x 0.075"	3.37" x 2.125" x 0.033"	3.37" x 2.125" x 0.033"	3.37" x 2.125" x 0.033"	2" x 1.24" x 0.38"	2" x 1.24" x 0.38"	1.77" x 1.18" x .06"	1.77 x 1.18 x 0.06
Slot punch (printed guide)	Vertical (punched)	Vertical (punched)	Vertical or horizontal	Vertical or horizontal	Vertical or horizontal	Keyring	Keyring	Keyring	Keyring
Memory capacity; application sectors	1K byte/8k bit; 16 sectors	2K byte/16k bit	1K byte/8k bit; 16 sectors	8k bit/1K byte	2K byte/16k bit	1K byte/8k bit; 16 sectors	2K byte/16k bit	1K byte/8k bit; 16 sectors	1K byte/8k bit
Warranty	Limited lifetime - Credentials have a lifetime warranty against manufacturers defects. See sales policy for complete warranty details.								



125 kHz+13.56 MHz

Multi-technology credentials¹

Model number	9951	5951	8920	9691T	5691T
Credential type	ISO glossy white ²	ISO glossy white ²	ISO glossy white ²	Thin keyfob	Thin keyfob
Credential technology; ISO standard	Proximity + MIFARE Classic; ISO 14443	Proximity+ MIFARE Plus SE; ISO 14443	Proximity + MIFARE DESFire™ EV1; ISO 14443	Proximity + MIFARE Classic; ISO 14443	Proximity+ MIFARE Plus SE; ISO 14443
Dimensions (H x W x D)	3.37" x 2.125" x 0.033"	1.77 x 1.18 x 0.06	3.37" x 2.125" x 0.033"	1.77" x 1.18" x .06"	3.37" x 2.125" x 0.033"
Slot punch (printed guide)	Vertical/horizontal	Keyring	Vertical/horizontal	Keyring	Vertical or horizontal
Memory capacity; application sectors	1K byte/8k bit; 16 sectors	1K byte/8k bit	2K byte/16k bit	1K byte/8k bit; 16 sectors	1K byte/8k bit
Warranty	Limited lifetime - Credentials have a lifetime warranty against manufacturers defects. See sales policy for complete warranty details.				

¹ For a complete list of available higher memory capacity and differing form factor smart and multi-technology credentials please contact Allegion Sales or see the Allegion Electronic Access Control catalog.

² ISO glossy white style credentials are made from composite material, are printable, and can include a magnetic stripe as an option. Add M1 to the model number for a magnetic stripe when ordering. Vertical slot punch not available on magnetic stripe cards.

Allegion, the Allegion logo, Schlage, the Schlage logo and Schlage Control are trademarks of Allegion plc, its subsidiaries and/or affiliates in the United States and other countries. All other trademarks are the property of their respective owners.

About Allegion

Allegion (NYSE: ALLE) is a global pioneer in safety and security, with leading brands like CISA®, Interflex®, LCN®, Schlage®, SimonsVoss® and Von Duprin®. Focusing on security around the door and adjacent areas, Allegion produces a range of solutions for homes, businesses, schools and other institutions. Allegion is a \$2 billion company, with products sold in almost 130 countries. For more, visit www.allegion.com.

