



**LHR SHOWN**  
**RHR OPPOSITE**

**INSTALLATION INSTRUCTIONS**

1. PREPARE INSIDE FACE OF DOOR FOR DEVICE.
    - A. SEE DEVICE DIRECTIONS FOR LOCATIONS OF VERT. AND DEVICE REF. CENTERLINES.
  2. PREPARE OUTSIDE FACE OF DOOR FOR TRIM.
    - A. TRANSFER VERT. AND DEVICE REF. CENTERLINES FROM INSIDE FACE TO OUTSIDE FACE OF DOOR. BE SURE VERT. CENTERLINE IS PARALLEL TO EDGE OF DOOR.
    - B. LOCATE AND PREPARE ALL HOLES AS INDICATED.
  3. INSTALL CYLINDER TO TRIM (IF REQUIRED).
  4. INSTALL TRIM.
    - BOTTOM PULL MOUNTING:  
1/4"-20x2-1/4" FPHMS FINISH WASHER
    - TOP TWO MOUNTING STUDS:  
ARE THRU-BOLTED TO DEVICE WHEN DEVICE IS INSTALLED.
- NOTE: FOR F-911-R DEVICES, INSERT SEXBOLTS INTO TWO HOLES PRIOR TO INSTALLING TRIM.**
5. CUT CYLINDER TAILPIECE (IF REQUIRED) SO THAT IT PROJECTS 1/8" TO 3/16" FROM THE SKIN OF DOOR.
  6. INSTALL DEVICE ON DOOR PER DEVICE INSTRUCTIONS.

**LSDA**

TITLE:  
**"DT" & "NL" CONTROL TRIM  
FOR (F)911 SERIES DEVICES**