



INSTALLATION INSTRUCTIONS

1. PREPARE INSIDE FACE OF DOOR FOR DEVICE.
 - A. SEE DEVICE DIRECTIONS FOR LOCATIONS OF VERT. AND DEVICE REF. CENTERLINES.
2. PREPARE OUTSIDE FACE OF DOOR FOR TRIM.
 - A. TRANSFER VERT. AND DEVICE REF. CENTERLINES FROM INSIDE FACE TO OUTSIDE FACE OF DOOR. BE SURE VERT. CENTERLINE IS PARALLEL TO EDGE OF DOOR.
 - B. LOCATE AND PREPARE ALL HOLES AS INDICATED.
3. INSTALL TRIM ON DOOR AND CUT LEVER SPINDLE TO SIZE.
 - A. TRIM MOUNTING.
 - FOUR STUDS: ARE THRU-BOLTED TO DEVICE WHEN DEVICE IS INSTALLED.
 - B. CUT LEVER SPINDLE.
 - VERTICAL & THREE POINT LATCH: LEVER SPINDLE TO EXTEND 5/8"-3/4" BEYOND DOOR SKIN.
 - MORTISE: LEVER SPINDLE TO BE INSIDE DOOR SKIN BY 1/4".
4. ASSEMBLE CYLINDER (IF REQUIRED).
 - A. IF USING MORTISE CYLINDER, INSTALL CYLINDER TO MORTISE LOCK.
 - B. IF USING RIM CYLINDER, CUT TAILPIECE TO EXTEND 3/8" BEYOND INSIDE FACE OF DOOR.
5. INSTALL DEVICE ON DOOR PER DEVICE INSTRUCTIONS.

NOTE: DIMENSIONS "A" & "B" ARE THE SAME FOR LE & SE TRIM REGARDLESS OF TRIM FUNCTION

CORRESPONDS TO TEMPLATES T-2102 AND W-2102

DEVICE	"A"	"B"	DEVICE	"A"	"B"
(F)XX-M-LE	1-1/4"	OMIT	(F)18-M-LE (NL)	1-1/4"	OMIT
(F)XX-M-LE (LS/LK)	OMIT	OMIT	(F)18-M-LE DT	OMIT	OMIT
(F)XX-M-LE (NL)	1-1/4"	OMIT	(F)18-M-P x LE DT	1-1/4"	OMIT
(F)XX-M-LE DT	OMIT	OMIT	(F)18-M-LE2	1-1/4"	OMIT
(F)XX-M-P x LE DT	1-1/4"	OMIT	(F)18-V-LE	1-1/4"	OMIT
(F)XX-M-LE2	1-1/4"	OMIT	(F)18-V-LE (LS/LK)	OMIT	OMIT
(F)XX-V-LE	1-1/4"	OMIT	(F)18-V-LE (NL)	1-1/4"	OMIT
(F)XX-V-LE (LS/LK)	OMIT	OMIT	(F)18-V-LE DT	OMIT	OMIT
(F)XX-V-LE (NL)	1-1/4"	OMIT	(F)18-V-P x LE DT	OMIT	1-1/4"
(F)XX-V-LE DT	OMIT	OMIT	(F)18-V-LE2	OMIT	1-1/4"
(F)XX-TPL-LE	1-1/4"	OMIT	(F)18-V-LE(20.C.)	1-1/4"	1-1/4"
(F)XX-TPL-LE (LS/LK)	OMIT	OMIT	(F)18-TPL-LE	1-1/4"	OMIT
(F)XX-TPL-LE (NL)	1-1/4"	OMIT	(F)18-TPL-LE (LS/LK)	OMIT	OMIT
(F)XX-TPL-LE DT	OMIT	OMIT	(F)18-TPL-LE (NL)	1-1/4"	OMIT
(F)18-M-LE	1-1/4"	OMIT	(F)18-TPL-LE DT	OMIT	OMIT
(F)18-M-LE (LS/LK)	OMIT	OMIT			

MONARCH
Exit Devices & Door Hardware

TECHNICAL SERVICE / CUSTOMER SERVICE 800-826-5972
FAX-ON-DEMAND 877-454-9696

TITLE: **LE & SE TRIMS FOR (F)18 & (F)XX SERIES SURFACE VERTICAL ROD, MORTISE AND THREE POINT LATCH DEVICES**

FOR LE & SE TRIM FOR (F)18 & (F)XX RIM, SEE OTHER SIDE

DATE: 3-1-98

DIRECTION SHEET - REV.

D-2102-4