

TEMPLATE FOR INSTALLING  
SCHLAGE

**A170**  
DUMMY TRIM

FOLD HERE  
ON EDGE  
OF DOOR



SCREW HOLES FOR  
ATTACHING MOUNTING PLATE



2<sup>3</sup>/<sub>8</sub>" BACKSET



INSTALL WITH  
KNOB CATCH  
TOWARD  
DOOR EDGE

SURFACE  
INSTALLATION

(Mark for screw holes  
at points  
indicated by  
small arrows.)



SEE REVERSE BEFORE INSTALLING

## **DIRECTIONS:**

1. Draw height line for Dummy Trim across edge of door (suggested height is 38" from floor). When installing on inactive leaf of a pair of doors, dummy trim should be installed at same height line and backset (distance from edge of door to center of lock trim) as the lock on the active door.
2. Place template on door and mark door through template (3) holes for attaching mounting plate.
3. Prepare dummy trim for installation as follows: Insert small screw driver through hole in side of knob shank and apply pressure. Slide knob off spindle. Remove rose, place mounting plate on door and line up in position with marks for screw holes. Insert screws and tighten. Place rose in position and snap over spring clip on mounting plate. (Threaded roses are unmounted and mounted by rotating bushing with spanner wrench.) Place knob on spindle and push into position.



### **Customer Service**

1-877-671-7011

[www.allegion.com/us](http://www.allegion.com/us)

© Allegion 2014  
Printed in U.S.A.  
P507-199 Rev. 01/14-b