


THIS DIAGRAM REPRESENTS A GENERIC CONFIGURATION. CUSTOM WIRING DIAGRAMS CAN BE ACQUIRED BY CONTACTING TECHNICAL SUPPORT.



NOTES:
1) ALL LOW VOLTAGE WIRING TO BE STANDARD.
MULTI-CONDUCTOR COLOR CODED WITHOUT SPLICES. 5) ADDITIONAL WIRING WILL BE REQUIRED FROM ACP THAT IS NOT SHOWN HERE. CONSULT PROVIDER FOR DETAILS. 4) THIS DRAWING IS FOR GRAPHICAL REPRESENTATION OF PRODUCTS DETAILED IN THE HARDWARE SET ONLY. 3) REFER TO SPECIFIC PRODUCT INSTALLATION INSTRUCTIONS FOR SPECIFIC WIRING REQUIREMENTS. 2) WIRING TO CONFORM TO APPLICABLE NATIONAL, STATE AND LOCAL ELECTRICAL CODES.

> HARDWARE USED: 1 FALCON 8200 AO 2 8310-813 TOUCHLESS ACTUATOR

> > OPERATION:
> > SINGLE BATHROOM DOOR ENTRANCE, NON FIRE RATED, NO POSITIVE LATCHING.

EXTERIOR WAVING HAND IN FRONT OF 8310-813 TOUCHLESS ACTUATOR TO SIGNAL FALCON 8200 AO TO OPEN OR DOOR MAY BE PULLED OPEN MANUALLY VIA PULL ON DOOR

INTERIOR WAVING HAND IN FRONT OF 8310-813 TOUCHLESS ACTUATOR**TILE: TO SIGNAL FALCON 8200 AO TO OPEN OR DOOR MAY BE PUSHED OPEN FROM INSIDE.

03-27-20 04-03-20

TYPE
ON LATCHING BATHROOM DOOR WITH
TOUCHLESS ACTUATORS INTERIOR AND
EXTERIOR

ALLEGION

NON LATCHING BATHROOM DOOR WITH TOUCHLESS ACTUATORS INTERIOR AND EXTERIOR

WIRING DIAGRAM DWG NO: 113521W

DRAWN/CHECKED BY:
B DOVE/J WEISS