




**Grade 2 deadlatch**

# B250 Series

**Overview**


Ideally suited for pool, apartment and condominium gates, utility panels and pipe chases, the Schlage B250 Series is tough, reliable and has a proven design that has been the industry standard for decades.




**Finishes**



**605**  
Bright Brass



**606**  
Satin Brass



**609**  
Antique Brass




**613**  
Oil Rubbed  
Bronze



**622**  
Matte Black



**625**  
Bright Chrome




**626**  
Satin Chrome




## Functions

Schlage functions that include an "F" designation denote fire rated options.



**Schlage B250**  
**ANSI E0122**  
**Single cylinder deadlatch**

- Deadlatch retracted by key outside or thumbturn inside
- Holdback feature standard
- Rotating thumbturn and activating holdback feature keeps latch retracted



**Schlage B252**  
**ANSI E0112**  
**Double cylinder deadlatch**

- Deadlatch retracted by key either side
- No holdback

Caution: Double cylinder locks on residences and any door, in any structure, which is used for egress are a life safety hazard in times of emergency and their use is not recommended. Installation should be in accordance with existing codes only.



Key



Thumbturn



## Cylinders

### Conventional cylinder

<b>P</b>	6-pin Conventional, keyed 5
<b>P6</b>	6-pin Conventional, keyed 6 (standard)
<b>Z</b>	SL 7-pin Conventional (A2 pinning)
<b>L</b>	Less Conventional

### Full size interchangeable core (FSIC)

<b>R</b>	6-pin FSIC
<b>M</b>	SL 7-pin FSIC (A2 pinning)
<b>J</b>	Less FSIC
<b>T</b>	Refundable FSIC construction core



## Specifications

### Chassis

Material	Wrought or forged brass or bronze, or pressure cast zinc.
Door thickness	1 <sup>3</sup> / <sub>8</sub> " to 1 <sup>3</sup> / <sub>4</sub> " (35 mm to 44 mm) standard. Available to 2 <sup>1</sup> / <sub>4</sub> " (57 mm), assembled to order.

### Latchbolt

Backset	Standard: 2 <sup>3</sup> / <sub>8</sub> " (60 mm) Optional: 2 <sup>3</sup> / <sub>4</sub> " (70 mm)
Faceplate	1 <sup>1</sup> / <sub>8</sub> " x 2 <sup>1</sup> / <sub>4</sub> " (29 mm x 57 mm) square corner, beveled. Brass, bronze or stainless steel.
Bolt	Brass, <sup>9</sup> / <sub>16</sub> " (14 mm) throw, deadlocking on keyed and exterior functions.
Strike	1 <sup>1</sup> / <sub>8</sub> " x 2 <sup>3</sup> / <sub>4</sub> " (32 mm x 70 mm) with steel reinforcer and two 3" screws standard.

### Keying

Cylinder format	6-pin Conventional (standard); also available in FSIC and 7-pin SL cylinder.
Keyway	Patented Everest 29 S123 (standard); also available in open, restricted, and Primus XP security levels with available master keying and construction keying.

### Attachment

Three 3" screws metal dustbox to frame. <sup>1</sup>/<sub>4</sub>" machine screws through bolt to firmly anchor lock to door.

### Warranty

3-year limited mechanical warranty. See price book for details.

### Certifications

ANSI/BHMA	A156.36-2010, Grade 2. BMHA certified.
Federal	BAA compliant.
Other	ADA compliant.