

VON DUPRIN®

Exit devices

55 Series

Overview

The 55 Series is a narrow stile device with a classic look that's ideal for retro-inspired architecture and historical buildings. Several mechanical, electronic and finish options can be customized to meet the needs of your facility. Take advantage of field reversible handing and flexible field sizing for several surface-mounted vertical rod and rim applications.



Device types



Rim device



75 Mortise lock device



47 Concealed vertical rod device,
5/16" throw



47WDC Wood door concealed
vertical rod exit device

Finishes



605
Bright Brass



606
Satin Brass



612
Satin Bronze



613
Oil Rubbed
Bronze



625
Bright Chrome



626
Satin Chrome



643e
Aged Bronze



693
Black


Due to the many variations in monitors and printers, color samples may appear different than the physical product. Contact your local sales representative for a physical color sample.

Trim functions



EO No outside trim

- Exit only




DT Dummy trim

- Pull when dogged (not recommended for fire device)
- Handed



L Lever

- Key locks and unlocks
- 1 ¼" mortise cylinder
- Handed, reversible lever
- Electrified lever operation available



NL Night latch

- Key retracts latchbolt
- Rim or 1 ¼" mortise cylinder
- Handed



TL Turn lever

- Key locks and unlocks (use with DT trim)
 - 1 ¼" mortise cylinder
-

Trim styles



550DT



550DT x 110MD



379L



375L



555NL



376L



550DT x 376T



371L



609DT x 376T



556NL



376 WDC-L



550DT x 376WDC-T

Trim styles

Dimensions

Trim style	Base width	Base height	Projection
550DT	3 ⁵ / ₈ "	11 ⁹ / ₁₆ "	2 ⁵ / ₈ "
379L	1 ¹¹ / ₁₆ "	7 ¹ / ₂ "	2 ⁵ / ₈ "
375L	2"	10 ¹ / ₂ "	2 ⁵ / ₈ "
555NL	3 ⁵ / ₈ "	11 ⁹ / ₁₆ "	2 ⁵ / ₈ "
376L	1 ¹¹ / ₁₆ "	7 ¹ / ₂ "	2 ⁵ / ₈ "
376T	1 ¹¹ / ₁₆ "	7 ¹ / ₂ "	1 ¹³ / ₁₆ "
371L	1 ¹¹ / ₁₆ "	7 ¹ / ₂ "	2 ⁵ / ₈ "
609DT	1 ⁹ / ₁₆ "	13"	1 ¹³ / ₁₆ "
556NL	3 ⁵ / ₈ "	11 ⁹ / ₁₆ "	2 ⁵ / ₈ "
376WDC-L	1 ¹¹ / ₁₆ "	7 ¹ / ₂ "	2 ⁵ / ₈ "
376WDC-T	1 ¹¹ / ₁₆ "	7 ¹ / ₂ "	1 ¹³ / ₁₆ "

Lever styles

Standard levers



01



02

- Knurling available



03

- Knurling available



06

- Default lever
- Suites with Schlage Rhodes
- Knurling available



07

- Suites with Schlage Athens



12

- Handed




17

- Suites with Schlage Sparta
- Knurling available

Dimensions

Lever	Width	Projection
01	4.0"	2.1"
02	4.75"	2.3"
03	4.75"	2.813"
06	4.7"	2.1"
07	4.6"	2.3"
12	4.3"	2.9"
17	4.7"	2.3"



Options

Electrified options

- RX Request to exit**
- Signals use of an opening
 - SPDT switch to monitor pushpad
 - 2 A maximum @ 24VDC; below 50 mA @ 24VDC for low current option

Electric unlocking

- E7500 Available on the following mortise lock devices: 5575L-BE, 5575L-BE-F**
- Voltage: 12 or 24VDC
 - Current: 0.60 amps @ 12VDC, 0.30 amps @ 24VDC

- E-trim Available as special order for the following BE trims: 376L-BE, 376WDC-L-BE and 379L-BE**
- Voltage: 12 or 24 VDC
 - Current: 1.0 amps @ 12VDC
 - 0.5 amps @ 24VDC

Latches

- ES Pullman latch**
- Pullman top latch for 5547 (metal doors, LBR only)
 - Most commonly used in conjunction with electric strikes and LBR-less bottom rod application

Crossbar

- KN Knurled crossbar**
- Tactile warning applied to device
- RCB Reinforced crossbar**

Centerline options

- NY5547 Centerline options for L, LBE, LDT**
- Lever at 45 ¹³/₁₆"
 - Device at std centerline 39 ¹³/₁₆" from finished floor
 - Up to 10" opening (metal doors)

- NYCA5547 Centerline options for L, LBE, LDT**
- Lever at 44"
 - Device at centerline 38" from finished floor
 - Up to 8' opening (metal doors)

Options

Matrix shows available options per device type but does not represent compatibility across multiple options.

	Electrified options	Electric unlocking				Latches	Crossbar		Centerline options	
	RX	E7500	E376L-BE	E376WDC-L-BE	E379L-BE	ES	KN	RCB	NY5547	NYCA5547
55	▪				▪		▪	▪		
5575	▪	▪					▪	▪		
5575-F	▪	▪					▪	▪		
5547	▪		▪			▪	▪	▪	▪	▪
5547-F	▪		▪				▪	▪		
5547WDC	▪			▪			▪	▪		
5547WDC-F	▪			▪			▪	▪		

Specifications

Accessibility	<ul style="list-style-type: none">Force to depress crossbar<ul style="list-style-type: none">Standard device: 15 lbsCrossbar projection<ul style="list-style-type: none">Neutral: 3 ³/₄" (95 mm)Depressed: 2 ³/₈" (60 mm)
Certifications/ approvals	All Von Duprin 55 Series exit devices are ANSI/BHMA Certified. Please refer to the BHMA Certified Products Directory for specific listings.
Mounting height	39 ¹³ / ₁₆ " (1011 mm) 39 ¹¹ / ₁₆ " (1008 mm) with mullion
Warranty	36 months from the date of placing the product in operation

Dimensions

