



Von Duprin 33A/35A Series Exit Devices Allegion

Final Assembly: Indianapolis, Indiana, USA

Life Expectancy: 25 Year(s)

End of Life Options: Recyclable (99%), Landfill (1%)

Ingredients:

ASTM A228 Steel; UNS G10080 Steel; Steel (unconfirmed alloy number); UNS G10180 Steel; UNS G12144 Steel; UNS A96063 Aluminum Alloy; UNS A83003 Aluminum Alloy; UNS G86200 Steel; UNS S30403 Stainless Steel; Nylon-66; UNS G10060 Steel; UNS G10500 Steel; ASTM AC41A Zinc Alloy; FC-0205-35 Powder Steel; Stainless Steel (unconfirmed alloy number); UNS A03800 Aluminum Alloy; UNS S30100 Stainless Steel; AISI 10B21 Steel; Glass Fiber; AA 6560 Aluminum Alloy; FX-1008-50 Powder Steel; UNS G10100 Steel; Carbon Filler; Zinc; 2-Propenenitrile, polymer with 1,3-butadiene

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: Not Applicable

I-14 Responsible Sourcing: Not Applicable

AGN-0006

EXP. 01 APR 2024

Original Issue Date: 2019